

**CONFIDENTIAL**

3-OCT 1958  
15103  
13972

Copy 272  
RM E58G11a

NACA RM E58G11a

TECH LIBRARY KAFB, NM  
DL43891



# RESEARCH MEMORANDUM

A PIVOTING-COWL-AND-SPIKE TECHNIQUE FOR EFFICIENT  
ANGLE-OF-ATTACK OPERATION OF SUPERSONIC INLETS

By Nick E. Samanich and Robert W. Cubbison

Lewis Flight Propulsion Laboratory  
Cleveland, Ohio

Classification cancelled (or changed to) UNCLASSIFIED

By Authority: NASA TECH PUB ANNOUNCEMENT #32  
(OFFICIAL USE - NOT TO BE REPRODUCED)

By: 16 Feb 61

APPROVED: [Signature]  
ANG G CHANG, JR.

DATE: 16 Mar 61

UNCLASSIFIED DOCUMENT

This material contains information affecting the National Defense of the United States within the meaning of the espionage laws, Title 18, U.S.C., Secs. 793 and 794, the transmission or revelation of which in any manner to an unauthorized person is prohibited by law.

## NATIONAL ADVISORY COMMITTEE FOR AERONAUTICS

WASHINGTON

September 23, 1958

**CONFIDENTIAL**

7057



## NATIONAL ADVISORY COMMITTEE FOR AERONAUTICS

RESEARCH MEMORANDUMA PIVOTING-COWL-AND-SPIKE TECHNIQUE FOR EFFICIENT  
ANGLE-OF-ATTACK OPERATION OF SUPERSONIC INLETS\*

By Nick E. Samanich and Robert W. Cubbison

## SUMMARY

A technique to obtain efficient inlet performance over an angle-of-attack range at supersonic Mach numbers has been investigated. The system utilizes a pivoting spike and attached cowl-lip shell to maintain inlet alignment with the airstream at all attitudes. Two isentropic compression spikes of  $35^\circ$  and  $39^\circ$  total turning were examined with the pivoting system. Critical pressure recovery of the  $35^\circ$  compression spike inlet was essentially constant at 77 percent with only a 2-percent loss in mass-flow ratio and a maximum distortion value of 7 percent when the nacelle angle of attack was increased from  $0^\circ$  to  $14^\circ$  at the design free-stream Mach number of 3.0. Peak pressure recoveries of 80 and 86 percent were obtained at Mach 3.0 with the  $35^\circ$  and  $39^\circ$  compression spike inlets, respectively. Performance parameters at Mach numbers of 2.0 and 2.5 are also presented.

## INTRODUCTION

Optimum performance over an angle-of-attack range is desirable for all types of aircraft and, in some cases, essential (for highly maneuverable aircraft). For high Mach numbers (greater than 2.0) a multicompression surface is usually required to give acceptable inlet performance, and the shock structure emanating from such a surface usually determines the cowl-lip location for optimum performance at zero angle of attack. Large decreases in internal performance have been experienced by conventional fixed-geometry inlet systems operating at angle of attack and may be attributed to (1) the shock system no longer being on-design but falling inside or outside the inlet or both and causing flow disturbances along with a reduction in capture mass flow and (2) asymmetric flow entering the inlet.

---

\* Title, Unclassified.

~~CONFIDENTIAL~~

A number of techniques to alleviate the adverse flow conditions caused by conventional inlets operating at angle of attack have been made at low supersonic Mach numbers (refs. 1 to 7). All these techniques had some compromises in their designs, which resulted in unfavorable inlet flow conditions in some region of their angle-of-attack range. Higher design Mach numbers would probably amplify the penalties associated with these compromises.

A cowl-lip shell attached to a pivoting spike, the combination capable of alignment with the airstream direction, has the desirable characteristic of being on-design at all angles of attack. This report presents the results of an investigation in which this technique was incorporated in the design of a high-performance Mach number 3.0 inlet tested at Mach numbers of 2.0, 2.5, and 3.0, a Reynolds number of  $2.5 \times 10^6$  per foot, and over an angle-of-attack range from  $0^\circ$  to  $14^\circ$ .

## SYMBOLS

$A_{in}$	inlet capture area, 1.183 sq ft
$A_{max}$	maximum projected frontal area of model, 1.483 sq ft
$A_x$	area normal to flow direction in duct
$A_3$	diffuser-exit flow area, 0.961 sq ft
$C_D$	drag coefficient, $D/q_0 A_{max}$
$D$	drag
$M$	Mach number
$m_3/m_0$	inlet mass-flow ratio, $\rho_3 V_3 A_3 / \rho_0 V_0 A_{in}$
$P$	total pressure
$\bar{P}_3/P_0$	total-pressure recovery
$\frac{P_{3,max} - P_{3,min}}{\bar{P}_3}$	distortion parameter
$q$	dynamic pressure
$V$	velocity
$x$	distance along axis of symmetry

5063

~~CONFIDENTIAL~~

$\alpha$	angle of attack, deg
$\theta_1$	cowl-position parameter, angle between axis of symmetry and line from spike tip to cowl lip, deg
$\rho$	density of air
Subscripts:	
e	external
max	maximum
min	minimum
0	conditions in free stream
3	conditions at diffuser exit
Superscript:	
—	area-weighted value

#### APPARATUS AND PROCEDURE

A photograph of the test model at angle of attack with the inlet aligned with the free-stream direction is shown in figure 1. The test vehicle, a 16.46-inch-diameter, 102-inch-long model, had a movable exit plug to control the back pressure. Provisions for spike translation, as well as inlet pivoting, were also incorporated. Forces were measured with an internal strain-gage balance. A schematic drawing of the test model, with a cutaway view of the pivoting inlet, is shown in figure 2.

Two isentropic spikes were designed from the method of reference 8 to have focused compression at Mach 3.0 with total turning of  $35^\circ$  and  $39^\circ$ , corresponding to a  $\theta_1 = 23.65^\circ$  for both spikes. The cowl shell had a sharp-edged lip with  $32^\circ$  and  $29^\circ$  external and internal lip angles, respectively, (for both spikes) and a projected area 20 percent of the maximum frontal area. The cowl lip was attached to the spike with three aerodynamically contoured struts. The spike-cowl shell combination was remotely pivoted with an internally housed screw jack. All the pivoting components that had metal-to-metal contact were of spherical design to permit rotation about a fixed center with a minimum of air leakage. The spikes were designed with the capability of  $1\frac{1}{2}$  inches of remotely

controlled translation in the constant-diameter portion of the centerbody immediately aft of the spike shoulder. This design permitted spike translation regardless of the spike-cowl shell angular position.

The bleed systems used with the  $35^\circ$  and  $39^\circ$  compression spike inlets are shown in detail in figure 3. The bleed mass flow was ducted out from the centerbody through two hollow struts and ejected to the airstream through two reverse-facing semiconical outlets located on the outer skin of the model (see fig. 1).

Total-pressure instrumentation was located at stations 1.8, 6.4, and 68 inches from the cowl lip. The total-pressure recovery was obtained from an area-weighted average of 48 total-pressure probes at station 68. The mass-flow ratio was calculated using the static pressure at station 68 and the assumption of isentropic flow to a choked area at the plug exit.

The geometry of the pivoting inlet components dictated the initial portion of the diffuser design. The internal area variation for optimum performance calculated from experimental data by the method of reference 9 at Mach numbers of 2.0, 2.5, and 3.0 with respective cowl-position parameters of  $24.40^\circ$ ,  $24.25^\circ$ , and  $23.65^\circ$  is presented in figure 4.

The investigation was conducted in the Lewis 10- by 10-foot supersonic wind tunnel at free-stream Mach numbers of 2.0, 2.5, and 3.0 and a Reynolds number of  $2.5 \times 10^6$  per foot.

## RESULTS AND DISCUSSION

Performance of the  $35^\circ$  compression spike inlet configuration at zero angle of attack over a Mach number range and at several cowl-position parameters is presented in figure 5. The Mach 3.0 on-design performance of the  $35^\circ$  compression inlet yielded a critical pressure recovery of 0.78, a drag coefficient of 0.15, and a distortion of 0.02. Only a small percentage of subcritical stability was noted at Mach 3.0. During operation in the unstable region, a static-pressure fluctuation as high as 65 percent of the free-stream total pressure was recorded at the compressor face. A bleed mass flow of approximately 5 percent of the inlet capture flow was removed from the spike surface at all the Mach numbers with the bleed system. Losses in total pressure through the diffuser at zero angle of attack near critical inlet operation are shown in figure 6. Eighty percent of the losses occurred in the initial 10 percent of the diffuser.

The performance of the inlet with pivoting cowl and spike as compared to the conventional fixed-geometry inlet is presented in figure 7

at a free-stream Mach number of 3.0 and a cowl-position parameter of  $23.60^\circ$ . The nacelle angle of attack could be increased from  $0^\circ$  to  $14^\circ$  with essentially no loss in critical pressure recovery (0.77) and with only a 0.02 loss in mass-flow ratio and a relatively slight increase in the distortion parameter (0.01 to 0.07). Losses of 0.11, 0.30, and 0.33 in critical pressure recovery, accompanied by respective losses of 0.01, 0.06, and 0.20 in mass-flow ratio, resulted when the fixed-geometry non-pivoted inlet was tested at angles of attack of  $5^\circ$ ,  $10^\circ$ , and  $14^\circ$ .

The effect of adding  $4^\circ$  of external compression to the  $35^\circ$  spike resulted in marginally better performance, however, the peak pressure recovery was increased from 80 to 86 percent. Figure 8(a) shows the performance of the  $39^\circ$  compression inlet at zero angle of attack over a range of cowl-position parameters, and figure 8(b) shows the effect of pivoting the cowl and spike through an angle-of-attack range. The results of the  $39^\circ$  compression inlet with pivoting (fig. 8(b)) were similar to those with the  $35^\circ$  compression inlet, which substantiates the effectiveness of the pivoting technique at angle of attack.

Figure 9 is a summary plot depicting the effect of angle of attack on the critical inlet performance with and without inlet pivoting at a Mach number of 3.0. In all cases where inlet pivoting was employed, the unfavorable effects associated with a conventional fixed-geometry inlet operating at angle of attack were virtually eliminated. It thus appears that the sharp turn occasioned by the pivoted cowl and spike in the subsonic portion of the diffuser had relatively little effect on the performance of this type of inlet and that all the adverse effects of angle of attack produced by the supersonic diffuser can be eliminated by aligning only a short portion of the nacelle with the free stream. Although drag data at angle of attack are not presented, the drag increment between the pivoted and nonpivoted configurations was a very small portion of the over-all nacelle drag and was within the accuracy of the balance measurements.

Total-pressure contours of the pivoted and nonpivoted  $35^\circ$  compression inlets at the diffuser exit for near critical operation over an angle-of-attack range are presented in figure 10. At all angles of attack, distortion was markedly reduced when the pivoting technique was employed. The largest degree of improvement in flow distortion along with elimination of any flow separation zones was noted at  $10^\circ$  and  $14^\circ$  angles of attack where distortions of 0.22 and 0.36 were reduced to 0.04 and 0.05, respectively, when inlet pivoting was employed.

Shock patterns at the inlet face at various Mach numbers and angles of attack with and without inlet pivoting are shown in the schlieren photographs in figure 11. Close examination of the shock structure at the design Mach number revealed the initial conical shock to be lying

slightly ahead of the coalescence of the weak shocks emanating from the isentropic surface. This shock orientation accounted for about 0.03 loss in mass-flow ratio when the inlet was operating on-design ( $\theta_7 = 23.65^\circ$ ).

#### SUMMARY OF RESULTS

A pivoting-cowl-and-spike technique for efficient angle-of-attack operation of supersonic inlets has been investigated with the following results at the design Mach number of 3.0:

1. There was essentially no loss in critical total-pressure recovery (0.77), only a 2-percent loss in mass-flow ratio, and a maximum distortion value of 0.07 when employing the pivoting  $35^\circ$  compression spike inlet over the model angle-of-attack range of  $0^\circ$  to  $14^\circ$ .

2. Peak pressure recoveries of 80 and 86 percent were obtained with the  $35^\circ$  and  $39^\circ$  compression spike inlets, respectively.

Lewis Flight Propulsion Laboratory  
National Advisory Committee for Aeronautics  
Cleveland, Ohio, July 16, 1958

#### REFERENCES

1. Leissler, L. Abbott, and Hearsh, Donald P.: Preliminary Investigation of Effect of Angle of Attack on Pressure Recovery and Stability Characteristics for a Vertical-Wedge-Nose Inlet at Mach Number of 1.90. NACA RM E52E14, 1952.
2. Beheim, Milton A.: A Preliminary Investigation at Mach Number 1.91 of an Inlet Configuration Designed for Insensitivity to Positive Angle-of-Attack Operation. NACA RM E53E20, 1953.
3. Beheim, Milton A.: A Preliminary Investigation at Mach Number 1.91 of a Diffuser Employing a Pivoted Cone to Improve Operation at Angle of Attack. NACA RM E53I30, 1953.
4. Johnston, I. H.: The Use of Freely Rotating Blade Rows to Improve Velocity Distributions in an Annulus. Memo. No. M.109, British NGTE, Feb. 1951.

5. Carter, Howard S., and Merlet, Charles F.: Preliminary Investigation of the Total-Pressure-Recovery Characteristics of a Symmetric and an Asymmetric Nose Inlet over a Wide Range of Angle of Attack at Supersonic Mach Numbers. NACA RM L53J30, 1953.
6. Dickie, George D., Jr.: Theoretical and Experimental Pressure Recovery of Sweptback Normal Shock Inlets. Jour. Aero. Sci., vol. 22, no. 3, Mar. 1955, pp. 189-193.
7. Schueller, Carl F., and Stitt, Leonard E.: An Inlet Design Concept to Reduce Flow Distortion at Angle of Attack. NACA RM E56K28b, 1957.
8. Connors, James F., and Meyer, Rudolph C.: Design Criteria for Axisymmetric and Two-Dimensional Supersonic Inlets and Exits. NACA TN 3589, 1956.
9. Weber, Richard J., and Luidens, Roger W.: A Simplified Method for Evaluating Jet-Propulsion-System Components in Terms of Airplane Performance. NACA RM E56J26, 1956.

5063









Figure 1. - Test model installed in 10- by 10-foot supersonic tunnel.





Schematic diagram of over-all test model.

Inlet and model at  
zero angle of attackInlet pivoted for angle-  
of-attack operation


Cutaway of pivoting spike and cowl assembly

CD-5962

Figure 2. - Experimental apparatus.



39° Spike compression bleed



35° Spike compression bleed

Detail A

Ram scoop coordinates for 35° and 39° bleeds, in.		
X	Radii	
	Y <sub>1</sub>	Y <sub>2</sub>
0	6.470	6.470
.05	6.483	6.499
.10	6.498	6.512
.15	6.504	6.520
.20	6.506	
.25	6.500	
.30	6.492	
.40	6.468	
.50	6.430	
.60	6.385	
.70	6.330	
.80	6.270	
.90	6.200	
1.00	6.130	

ED-5963

Figure 3. - Illustration depicting boundary-layer bleed systems.




Figure 4. - Internal area distributions for subsonic diffuser at optimum cowl-position parameters.




Figure 5. - Internal and external performance over a Mach number range of  $35^\circ$  compression spike inlet at zero angle of attack and various values of cowl-position parameter.

5063





Figure 6. - Location of total-pressure losses in subsonic diffuser for near critical operation at zero angle of attack. Free-stream Mach number, 3.0; cowl-position parameter, 23.60°.





Figure 7. - Effect of angle of attack on performance of  $35^\circ$  compression spike configuration with and without inlet-spike pivoting at a free-stream Mach number of 3.0 and a cowl-position parameter of  $23.60^\circ$ .

CONFIDENTIAL



(a) Varying cowl-position parameter at zero angle of attack.

(b) Cowl-position parameter,  $23.55^\circ$ ; angles of attack,  $0^\circ$ ,  $5^\circ$ ,  $10^\circ$ , and  $14^\circ$ ; inlet spike pivoted.

Figure 8. - Effect of cowl-position parameter and angle of attack on performance of  $39^\circ$  compression spike inlet at free-stream Mach number of 3.0.








Figure 9. - Effect of angle of attack on performance with and without inlet pivoting during critical Mach 3.0 operation.

5063


CY-3




Angle of attack,  $0^\circ$ ; total-pressure recovery, 0.79



Angle of attack,  $5^\circ$ ; total-pressure recovery, 0.68




Angle of attack,  $10^\circ$ ; total-pressure recovery, 0.51



Angle of attack,  $14^\circ$ ; total-pressure recovery, 0.45

(a) Without pivoting.

Figure 10. - Total-pressure contours at diffuser exit for near critical operation for  $35^\circ$  compression inlet with and without pivoting at free-stream Mach number of 3.0.




(b) With pivoting.

Figure 10. - Concluded. Total-pressure contours at diffuser exit for near critical operation for  $35^\circ$  compression inlet with and without pivoting at free-stream Mach number of 3.0.


5063

CY-3 back



Free-stream Mach number, 2.0



Free-stream Mach number, 2.5



Free-stream Mach number, 3.0

(a) Inlet operated supercritically at zero angle of attack over Mach number range investigated.

Figure 11. - Schlieren photographs of 35° compression spike inlet.

Angle of attack,  $5^\circ$ ; unpivotedAngle of attack,  $10^\circ$ ; unpivotedAngle of attack,  $5^\circ$ ; pivotedAngle of attack,  $10^\circ$ ; pivoted





(b) Inlet operated with and without inlet pivoting at several angles of attack.  
Free-stream Mach number, 3.0.

Figure 11. - Concluded. Schlieren photographs of  $35^\circ$  compression spike inlet.

NOTES: (1) Reynolds number is based on the diameter of a circle with the same area as that of the capture area of the inlet.

(2) The symbol \* denotes the occurrence of buzz.

## INLET BIBLIOGRAPHY SHEET

Report and facility	Description		Test parameters				Test data			Performance		Remarks		
	Configuration	Number of oblique shocks	Type of boundary-layer control	Free-stream Mach number	Reynolds number $\times 10^{-6}$	Angle of attack, deg	Angle of yaw, deg	Drag	Inlet-flow profile	Discharge-flow profile	Flow picture		Maximum total-pressure recovery	Mass-flow ratio
CONFID. RM E58011a 10- by 10-ft super-sonic wind tunnel		Isen-tropic	Ram scoop	2.0 to 5.0	2.89	0 to 14	0	✓		✓	✓	0.88	0.39* to 0.92	A pivoting cowl and spike technique for efficient angle-of-attack operation of supersonic inlets has been investigated for its effectiveness.
CONFID. RM E58011a 10- by 10-ft super-sonic wind tunnel		Isen-tropic	Ram scoop	2.0 to 5.0	2.89	0 to 14	0	✓		✓	✓	0.88	0.39* to 0.92	A pivoting cowl and spike technique for efficient angle-of-attack operation of supersonic inlets has been investigated for its effectiveness.
CONFID. RM E58011a 10- by 10-ft super-sonic wind tunnel		Isen-tropic	Ram scoop	2.0 to 5.0	2.89	0 to 14	0	✓		✓	✓	0.88	0.39* to 0.92	A pivoting cowl and spike technique for efficient angle-of-attack operation of supersonic inlets has been investigated for its effectiveness.
CONFID. RM E58011a 10- by 10-ft super-sonic wind tunnel		Isen-tropic	Ram scoop	2.0 to 5.0	2.89	0 to 14	0	✓		✓	✓	0.88	0.39* to 0.92	A pivoting cowl and spike technique for efficient angle-of-attack operation of supersonic inlets has been investigated for its effectiveness.

## Bibliography

These strips are provided for the convenience of the reader and can be removed from this report to compile a bibliography of NACA inlet reports. This page is being added only to inlet reports and is on a trial basis.

~~CONFIDENTIAL~~